



## Technical Data Sheet

### Food-Tek Dry PTFE Spray

**A clean, food grade, non toxic, dry film, non stick, low friction spray for food, beverage, pharmaceutical and other clean industries**

**Dry PTFE Spray** is a food grade, clean, non-toxic, non-stick lubricant developed for the lubrication of chutes, links, pins, rotating and small moving parts and open bearings. **Dry PTFE Spray** is an exceptionally versatile, odourless lubricant which does not attract dust and dirt, with an excellent temperature range to +270°C.

**Applications: -**

Industrial: Cams, followers, conveyors, slides and chutes, links and pins, open bearings and other moving parts

**Features and Benefits: -**

- |                                                                                                                                                                                                              |                                                                                                                                                                                       |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>➤ NSF H1 Registered</li> <li>➤ Excellent temperature range</li> <li>➤ Dry lubrication</li> <li>➤ Excellent anti-stick properties</li> <li>➤ Total dry film</li> </ul> | <p>Safe to use where incidental food contact may occur.<br/>-20°C to +270°C<br/>Does not attract dust and dirt<br/>Keeps production rates high<br/>Will not stress crack plastics</p> |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

**Method of Application: -**

Shake can thoroughly before use. Apply a thin even coating onto surface from approx 15 -30cm (6 to 12 inches). Apply **Dry PTFE Spray** sparingly. As with all aerosols, store in a cool, dry place, out of direct sunlight. Storage temperature should be below 50°C.

Part Number: 60104