



## Technical Data Sheet

### Food-Tek Spray Grease

**A food grade, synthetic, tacky, water resistant, high temperature spray grease for food, beverage, pharmaceutical and other clean industries**

**Spray Grease** is a premium quality, non toxic spray grease containing extreme pressure and anti-wear additives plus PTFE to increase wear resistance and load carrying capacity. **Spray Grease** is designed for all anti-friction and plain bearing applications requiring extreme temperature resistance, high load carrying and water resistance. It is ideal for applications that are difficult to get to, or require the convenience of an aerosol applied grease.

**Applications: -**

Use on plain and anti-friction bearings, bushes, slides and guides, high and low temperature applications. Excellent for wet and wash down areas, all heavy duty grease applications within the food and clean industries.

**Features and Benefits: -**

- |   |   |
|---|---|
| <ul style="list-style-type: none"> <li>➤ NSF H1 registered</li> <li>➤ Fully Synthetic</li> <li>➤ Contains PTFE</li> <li>➤ Excellent EP properties</li> <li>➤ Very High water resistance</li> <li>➤ High temperature resistance</li> </ul> | <p>Safe to use where incidental food contact may occur.</p> <p>long life, extended lubrication intervals</p> <p>Excellent anti-wear properties</p> <p>Resistant to shock loads, increased load carrying</p> <p>extends component life and lubrication intervals</p> <p>Continuous temperature range -50°C to +170°C</p> |
|---|---|

**Method of Application: -**

Shake can thoroughly before use. Apply a thin even coating onto surface from approx 15 -30cm (6 to 12 inches). Apply **Spray Grease** sparingly. Store in a cool, dry place, out of direct sunlight. Storage temperature should be below 50°C.

Part Number: 60106