



Technical Data Sheet

Indu-Tek Dry Moly Coating Spray

A premium dry film lubricant, leaving a Molybdenum Disulphide coating in place for high loads in Mining and Industrial applications

Dry Moly Coating Spray is a premium quality dry film lubricant, for use in all areas where a high load, dry coated surface is required to eliminate dust and dirt pick up and abrasion. **Dry Moly Coating Spray** utilises bonding agents to stick to the component surface and has very good resistance to water, it will protect components against corrosion in humid and wet conditions.

Applications: -

Industrial and mining: chains, slideways and gears, all sliding surfaces operating in dry, dusty and abrasive conditions. Also use in areas where conventional “wet” oils and greases cannot be used

Features and Benefits: -

- Fast bonding and drying
 - Fully water resistant
 - Dry Film
 - Excellent wear and load resistance
- Ready to use immediately
 - Extends component life and protects against corrosion
 - Protects against dust & dirt pick up and abrasion
 - Extends component life

Method of Application: -

Dry Moly Coating Spray is an aerosol product; Ensure surfaces to be treated are clean and dry. Shake can thoroughly for 2-3 minutes after agitator ball begins to rattle. Hold can upright and apply a thin even coating onto surface from approx 15 -30cm (6-12 inches). After use invert can and spray until spray colour is clear. **Dry Moly Coating Spray** will be touch dry in 2-3 minutes and completely cured in approximately 3 hours. The cured film can be improved by lightly burnishing with a clean lint free cloth.

Part Number: 61001