



## Technical Data Sheet

### Indu-Tek Multi-Lube Xtreme

**A superior synthetic, multi-purpose, extremely versatile oil fortified with PTFE for use in mining, rail, offshore and industrial applications**

**Multi-Lube Xtreme** is a premium quality extremely versatile lubricant fortified with a high degree of stable suspension PTFE to give superior lubricity and friction reduction and load carrying. It is designed for penetrating chains and threads as well as a general workshop fluid that will lubricate protect and clean components. **Multi-lube Xtreme** has anti-corrosion and anti-oxidation additives and a carrier fluid, which, when evaporated, leaves behind a durable lubricating film that protects against corrosion and reduces wear and friction. This non stick PTFE based film repels water, dust and other contaminants. This makes it ideal for sliding surfaces under load such as switch plates and other high wear applications.

**Applications: -**

Suitable for all types of chains, bearings, sliding surfaces, open lubrication points on machinery also prevents internal corrosion on wire ropes and as a general maintenance product to clean, protect, displace water, and lubricate all surfaces and components.

Switch plates and sliding chairs on rail ways.

**Features and Benefits: -**

- |                                    |   |
|------------------------------------|---|
| ➤ Fully Synthetic base oil         | Extreme long life, extended wet life of lubricant     |
| ➤ Excellent load carrying          | Extends life of components                            |
| ➤ Excellent penetrating properties | Frees up corroded nuts, bolts and threads             |
| ➤ Contains PTFE                    | Increased wear resistance                             |
| ➤ Truly multifunctional            | can replace many workshop products                    |
| ➤ Excellent coating product        | protects against fretting corrosion, wear and squeaks |
| ➤ Removes moisture and water       | prevents components form corroding                    |
| ➤ Wide Temperature range           | -40°C to +200°C                                       |

**Method of Application: -**

**Multi-lube Xtreme** can be applied by brush or dipped or in a suitable trigger spray. For penetrating threaded components and springs, allow time to penetrate. For best results, clean surface and remove old oil, dirt and grease, apply **Multi-lube Xtreme** sparingly.

Part Number: 51530

The content of this data sheet is given in good faith but without warranty